Please amend the specification as follows:

Page 2, line 19,

-- The applicant has developed a process to obtain polyglycolyl urea <u>hydantoin</u> from aromatic diglycinates, the main characteristic of which is that it does not form high risk polluting residual by-products such as HCN emission, obtaining a product that meets the main properties of such commercially available resins such as thermal, mechanical, and chemical properties and even improving certain characteristics such as freon resistance of polyesterimide-type enameled products.

Page 3, lines 4 and 6:

Hereinafter the invention will be described according to the process stages to obtain the polyglycolyl urea <a href="hydantoin">hydantoin</a> as well as its use, main object of the application, in the manufacturing of H-class magnet-wire with improved properties.

The process to obtain polyglycolyl urea hydantoin PGU is divided in two main stages A and B.--

Page 3, lines 14 and 16:

- --Stage B includes the following steps:
- 4) loading [aromatic] <u>methyl</u> isocyanate, diglycinate, solvents and catalyst in the polymerization reactor;
- 5) obtaining polyglycolyl urea <u>hydantoin</u> resin;
- 6) adding polyester-type electro-insulating varnishes;
- 7) manufacturing H-class magnet-wire with improved properties. --

Page 4, lines 19 - 22 (end of the page), please delete the lines and replace with the following:

-- Path 2: nucleophilic shift

$$[CH_3 -O C-C-Cl + H_2N - Ar - NH_2 + N(CH_2-CH_3)_3 \\ \hline Pressure, 90^{\circ} C \\ Methylchloro- methlyene triethyl \\ Propionate dianiline amine]$$

O
$$|\cdot|$$
-- ClCH<sub>2</sub> - O - C - Et + H<sub>2</sub>N - Ar - CH<sub>2</sub> Ar - NH<sub>2</sub> + N(CH<sub>2</sub> - CH<sub>3</sub>)<sub>3</sub>

Methylchloropropionate methylenedianiline triethylamine --

Page 5, line 12, please add the following:

Obtainment of methyl diglycinate from methylenedianiline

a) [in] In a glass or stainless steel matrass, provided with stirring means, reflux column, heating and cooling systems, the following materials are added: methylenedianyline, methanol, and methyl bromoproprionate. A  $C_1$ - $C_4$  aliphatic solvent may be used.

Page 7, beginning at line 4, please make the following amendment:

Once the theoretical distillate is recovered, heating is stopped, and the resin is cooled at 70° C to unload the corresponding containers, and a polyglycolyl urea hydantoin resin of the following